

LubeMax Anti-Wear Hydraulic Fluids

22, 32, 46, 68, 100




PRODUCT DESCRIPTION

LubeMax Anti-Wear (AW) Hydraulic Fluids are designed for high performance hydraulic systems. These fluids provide excellent operating and maintenance benefits for increased productivity.

APPLICATION OF PRODUCT

LubeMax Industrial Anti-Wear Hydraulic Fluids are recommended for vane, piston, or gear-type hydraulic pumps in heavy duty and industrial service.

Check your owner's manual for correct fluid viscosity



SPECIFICATIONS AND APPROVALS OF PRODUCT

LubeMax Anti-Wear Hydraulic Fluids are recommended for use where the following specifications are listed. Some specifications are viscosity grade specific. Refer to equipment owner's manual for correct viscosity grade recommendations.

- ASTM D6158
- Cincinnati/MAG IAS P-68 (AW 68,46, 32)
- Parker Denison HF-0, HF-1, HF-2
- Sperry Vickers/Eaton I-286-S, M-2950-S • Eaton E-FDGN-TB002-E, 35VQ25A
- US Steel 127, 136
- DIN 51524 Part 1, 2, 3
- General Motors LS-2
- JCMAS HK
- Bosch Rexroth

FEATURES AND BENEFITS OF PRODUCT

LubeMax Anti-Wear Hydraulic Fluids are manufactured with paraffinic base oils and high performance additives. They provide trouble free service in high output hydraulic systems at high temperature and pressure. This hydraulic fluid is designed to operate over a broad temperature range, resulting in lower maintenance cost and production downtime. LubeMax Anti-Wear Hydraulic Fluids have increased discharge flow rates and decreased internal pump leakage rates resulting in increased hydraulic system pumping efficiency, and therefore fewer fluid changes and less used fluid disposal. These hydraulic oils may also be used in general purpose lubricants where straight mineral oils and conventional rust and oxidation inhibited oils are recommended.

LubeMax Anti-Wear Hydraulic Fluids deliver value through the following benefits:

- Long equipment life — anti-wear additives minimize wear by protecting surfaces even when heavy loads cause lubricant film breakdown.
- Minimized downtime — rust and oxidation inhibitor system helps prevent the production of rust formation as well as deposits, varnish, and sludge, which can damage metal surfaces and oil seals.
- Smooth operation — excellent fluid stability and water separation characteristics promote filterability even in the presence of water contamination. Anti-foam and air release properties help ensure smooth operation and high system efficiency.

Call: +14432041973 for more information.

LUBEMAX INDUSTRIAL EP GEAR LUBRICANTS

TYPICAL TECHNICAL PROPERTIES

PROPERTY	TEST METHOD	LubeMax				
		AW 22	AW 32	AW 46	AW 68	AW 100
Gravity; °API	ASTM D287	33.5	32.44	31.5	30.7	30.2
Specific Gravity @ 15.6°C	ASTM D4052	0.857	0.863	0.868	0.872	0.875
Viscosity @ 40°C (cSt)	ASTM D445	22.0	31.6	45.60	68.0	100.0
Viscosity @ 100°C (cSt)	ASTM D445	4.5	5.55	7.02	9.05	11.5
Viscosity Index	ASTM D2270	114	116	112	110	105
Flash Point °C	ASTM D92	216	216	230	299	260
Pour Point °C	ASTM D5950	-44	-40	-36	-33	-30
Color	ASTM D1500	0.5	0.5	1.0	1.0	1.0
Zinc, wt %	ASTM D5185	0.041	0.041	0.041	0.041	0.041
Phosphorus, wt. %	ASTM D5185	0.033	0.033	0.033	0.033	0.033
Calcium wt. %	ASTM D5185	0.003	0.003	0.003	0.003	0.003
Sulfur, wt %	ASTM D4951	0.065	0.065	0.065	0.065	0.065
Oxidation hours (minimum)	ASTM D943	5000	5000	5000	5000	5000

HEALTH AND SAFETY

This product is not expected to have adverse health implications when used for its intended application. For detailed information on safe handling of this product, refer to its Material Safety Data Sheet (MSDS). To obtain an MSDS on this or any other LubeMax product, please visit www.lube-max.com or call +234 8053390168 or +1 443 204 1972. When disposing of used product, be responsible to the environment.

WHY WE ARE GOOD

LubeMax stands for robust, reliable, high quality products tailored to suit the requirements of the on- and off-road heavy duty, automotive and industrial markets. Our solutions span from trend-setting retail lubricants through small-batch custom formulations to large bulk orders ready for immediate delivery.

The extensive LubeMax product range includes premium oils, lubricants, greases, chemicals and specialty fluids formulated with virgin base oils and protective inhibitors. Designed to handle the most extreme climates and operating conditions, the LubeMax products protect and extend the life of your equipment, optimize performance and improve productivity while meeting and exceeding industry standards

LubeMax Lubricants

USA 1 443 204 1972

Nigeria +234 8053390168

Info@Lube-max.com **LUBEMAX**